

Capitalize on your passenger flow

EYES 3



EYES 3 - COUNTING CELL

- Counting the ins and outs with more than 98% precision
- Powered by AI
- Detection of u-turns
- 4 counting modes
- Distinction of adults, children, wheelchairs, strollers, bikes
- 3D stereoscopic technology

DATA PROCESSING

- Cells connected to the cloud
- Aggregated data, secured and ready to be processed
- Internal data backup for up to 1 year
- Exchange protocol SOAP
- Plug & Play - Ready to use

REAL TIME DATA VIA CALCULATOR

- Instant sending of counting data
- Aggregation of GPS positions with counting data
- Aggregation of time stamps with counting data
- Automatic alarm reporting

TECHNICAL DATA

Power supply POE 48V or 9 V DC - 75 V DC
Protected against short-circuits

Consumption 10 W

Operating temperature -25°C — +70°C

Box Aluminium

Dimensions (L x l x H) 95 mm x 59mm x 32 mm

Weight 250g

Standards IP64/ IK07
Certified to railway standards
CE/ EN50155 - EN 61000 - EN45545-2

MTBF > 1 000 000 h at 35°C

Field of vision 135°

Installation height From 1.90m to 3.50m



TRAMWAY




METRO



TRAIN



BUS



COACH



SALES & STATION

ADVANTAGES

- The smallest counting cell ever designed
- 4K resolution
- Wide angle counting area
- GDPR and NDPC compliance
- French product and support in France

THE PROS

- Remote status check and maintenance on the cloud
- Setup & updates via the cloud
- Recording of anonymized counting sequences
- Contradictory video counting available on the cloud
- On-board system interconnection possible

EASY INSTALLATION

- Easy set-up and integration thanks to the size of the cells
- Fits on single and double doors
- Accurate at all installation heights
- Configuration and testing via a user-friendly Web interface
- Automatic optimization of counting parameters

ACCESSORIES AND SERVICES

- Mechanical installation kit
- Wiring kit
- Installation and commissioning support service
- Monitoring SaaS of available equipment

INTERFACES

Communication	Ethernet/ WIFI/ RS485/ CAN
Protocols	SOAP, TCP, UDP, FTP, SSH
Logical inputs	1 programmable input (door signal)
Configuration	Via a web or remote interface
Compatibility	ITxPT

Contact : sales@webreathe.fr or webreathe.fr

WEBREATHE ALL RIGHTS RESERVED 2025

2FLOW

by WEBREATHE